



Technical Data Sheet

General data		
Frame size	80	
Housing material	Aluminum	
Install model	According to the standard	
Type of feet	Removable feet	
Net weight	12.5 kg	
Insulation class	F H	(Standard) (Optional)
Protection degree	IP 55 IP 56	(Standard) (Optional)
Thermal protection	Without Customizable	(Standard) (Optional)
Rotation direction	Clockwise Counter clockwise	(Standard) (Optional)
Service duty	S1	
Vibration level	A	
Balance	Half-key balanced	
Cable glands	1 - M20 × 1.5	
Cooling	IC 411	
Painting color	RAL 7024 Customizable	(Standard) (Optional)
Regulations	IEC / DIN / ISO / VDE / EN	
Standard	IEC 60034	

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	0.75	kW
Frequency	50	Hz
Voltage (±5%)	230 400 276 480	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	935 1120	RPM @ 50Hz RPM @ 60Hz
Rated current	3.77 2.18	A (In) @ Δ 50Hz A (In) @ Y 50Hz
Starting current	4.9	×In
Rated torque	7.66	Nm (Mn)
Starting torque	2.8	×Mn
Breakdown torque	3.1	×Mn
Efficiency	78.9 78.2 74.4	IE3 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.63	@ 100% load

Mechanical data		
Bearings brand	C&U Customizable	(Standard) (Optional)
Bearings type	6204 2RZ C3 6204 2RZ C3	(DE) (NDE)
Lifetime of bearings	20000 hours	
Allowed radial load Allowed axial load	863 N 752.68 N	
Grease type		
Lubrication interval of NDE bearing Lubrication interval of DE bearing	h h	
Moment of inertia	0.00323	Kg*m ²
Noise level	59	dB(A)

No. 303 Kangliu Road Kangqiao Town Pudong Shanghai, 201315, China

Tel: +86 (21) 6819 2006, Fax: +86 (21) 5812 9366, Email: info@techttop.net.cn, Website: www.techttop.com